

Aspire Rehab RX Advanced Tilt-In-Space Wheelchair



- **The Rehab RX** – is designed for the **more complex user**, who requires assistance with **positioning, re-positioning and skin management**
- **Tilt (26°) and backrest recline (30°)** – this facilitates weight re-distribution and the preservation of skin integrity. It also optimises user comfort, decreases user fatigue and assists with head control
- **Contoured, built-up backrest and seat cushion** – the backrest has a gentle lumbar build up and moderate lateral supports; together with the abductor and adductor build-up at the seat cushion, midline positioning is optimised
- **Advanced articulating legrests** – closely mimic the normal movement at the knee upon elevation, allowing the thigh to maintain contact with the seating surface, ensuring maximum support and skin contact with the cushion
- **Breathability** – support surfaces offer multi-layered foam with breathable multi-stretch covers - for pressure re-distribution, comfort and to enhance skin microclimate
- **Highly adjustable** – depth and width adjustable seat sizing. Height adjustable and removable armrests. Adjustable headrest
- **Crash Tested** – to AS/NZ3616.196
- Anti-tippers come as standard

Prescribing Therapists: Click here to download our [Clinical Assistance Guide](#)

Warranty Information

- 2 Years Frame
- 1 Year Components

✔ Contracted DVA product

✔ Contract approved

ndis

Item Code:

05_122203115_0105_1_2

Wheelchair Manual –

Composite:05_417_0105_1_2

Click [here](#) for more information

Compliance

AS3696-1:2008

Code	Display Name	Seat Depth	Seat Width	Backrest Height	Seat To Floor Height	Safe Working Load	Unit Weight	Colour	Material
MWS449710	Aspire Rehab RX - 410mm (16") - 460mm (18") Wide	440 - 530 mm	410 - 460 mm	460 - 710 mm	400 - 475 mm	180 kg	41.0 kg	Silver	Steel
MWS449720	Aspire Rehab RX - 460mm (18") - 510mm (20") Wide	440 - 530 mm	460 - 510 mm	460 - 710 mm	400 - 475 mm	180 kg	43.0 kg	Silver	Steel
MWS449740	Aspire Rehab RX - 510mm (20") - 560mm (22") Wide	470 - 560 mm	510 - 560 mm	460 - 710 mm	400 - 475 mm	180 kg	47.2 kg	Silver	Steel